

TECHNICAL DATA SHEET [TDS]

AAT-270 Anchor Bond Premium Adhesive

Anchor Bond Premium Adhesive is a *Go2 Adhesive* formulated for the installation of direct glue carpets and other types of floor covering. AAT's *Go2 Adhesive* formulas have been formulated to ensure adhesive performance under the very demanding conditions commonly found in today's fast paced construction. Anchor Bond is designed for direct glue downs of stiff and "boardy" carpets that have a tendency to curl or spring up after installation. Anchor Bond adhesive remains tacky for an extended period, and has excellent rebonding capabilities. Anchor Bond is a safe, light colored, low odor, 0 VOC adhesive designed with the installer's needs in mind. Anchor Bond is moisture resistant and non-flammable, and is a versatile, strong, trouble-free floor covering adhesive. This zero VOC adhesive is protected by the CleanGuard® two-stage antimicrobial. CleanGuard is a specifically formulated broad-spectrum, anti-microbial agent that protects our adhesives and sealers from microorganisms, such as mold or mildew, in both the wet and dry state.

Uses:

Anchor Bond is recommended for the following installations:

- Carpets: Woven Polypropylene (ActionBac®, hot melt, etc.) Latex Unitary, Urethane foam-backed (Enhancer® I,II,III,IV and Durafoam), Rubber Backs, Woven and needlepunch, Double Glue-Downs with approved carpet & cushion, Jute
- Resilient Flooring (Although this adhesive is formulated for carpet installations, because of its non-staining characteristics, it can be used to install the following.): felt backed sheet vinyl

NOTE: This adhesive is not recommended for pure vinyl backed sheet goods or carpets.



Anchor Bond Premium may contribute to the LEED certification of projects in the following categories:

- IEQ Credit 4.1—Low Emitting Materials – Adhesives & Sealants
- IEQ Credit 4.3—Low Emitting Materials – Flooring Systems
- IEQ Credit 5—Regional Materials

Sub-floor and Site Conditions:

Recommended Sub-floors ■ Concrete above, on or below grade ■ APA rated plywood underlayment ■ Properly prepared gypsum cement

Sub-floors on and below grade must be protected from ground moisture with a functioning and intact Class A vapor retarder that conforms to the requirements of the most current version of ASTM E-1745. This vapor retarder must be directly beneath, and in contact with, the slab. Concrete sub-floors must be properly prepared according to the practices detailed in the latest standard, ASTM F-710. Gypsum sub-floors must meet the requirements of the most current version of ASTM F-2419. All curing agents [topical and admix], adhesives, paints, varnishes, oils, waxes, dust, dirt and any other bond inhibiting substances must be removed. The removal of bond inhibiting substances must be by mechanical means: sanding, shot or bead blasting. Anchor Bond cannot be used if adhesive removers, solvent or chemical cleaners have been used.

The maximum moisture emission rate of the sub-floor cannot exceed 8lbs/1000 sq.ft./24 hours [ASTM F-1869], with a pH of 7.0- 9.0 [ASTM F-710], and a maximum *in situ* RH of 85% [ASTM F-2170]. Prior to the application of Anchor Bond, sub-floors must be tested in strict accordance to the most recent versions of ASTM F-1869 and F-2170. Both testing protocols must be performed in order to provide the most accurate view of the sub-floor's condition. Sub-floors of lightweight concrete must be tested in strict accordance to the most recent version of ASTM F-2170. The placement of calcium chloride kits and

humidity probes must follow the ASTM standards for proper locations and the correct quantity of test sites. These and other tests may be performed by AAT in the event of a warranty claim.

All sub-floors must be flat and structurally sound. Smooth or glazed surfaces must be abraded. Repair all joints and cracks with latex-based portland cement underlayments. Never sand existing resilient flooring that could contain asbestos. Follow all Federal, State and Local regulations relating to the removal of in-place, asbestos containing material. Very porous sub-floors must be primed with AAT-570 Primer.

NOTE: Strip or plank wood flooring, particleboard and OSB sub-floors should be covered with an approved underlayment (minimum thickness of ¼"). Anchor Bond cannot be used if adhesive removers, solvent or chemical cleaners have been used. Before beginning installations with backing systems or over sub-floors not listed contact AAT's Technical Services for recommendations. AAT Technical Services can be reached at 1(800)228-4583 or by email at techservice@aatglue.com. It is the sole responsibility of the applicator of this product to determine the suitability and compatibility of this product for their intended use. *If the provided preparation and application instructions are not followed, DO NOT USE Anchor Bond.*

Installation Recommendations:

Typical towels and approximate coverage: (depth x width x spacing)

Woven polypropylene, woven: 1/8" x 1/8" x 1/8" U notch, 100 sq. ft. /gal.

Attached cushions: 3/32" x 3/32" x 3/32" V notch, 125 sq. ft. /gal.

Unitary and Double-Glue (carpet to cushion): 1/8" x 1/8" x 1/16" U notch, 50 sq. ft./gal.

Felt backed Sheet Vinyl: 1/16" x 1/16" x 1/16" □ notch, 150 sq. ft./gal.

The building should be completely enclosed. All outside doors and windows should be properly installed with latching mechanisms in place. Adequate ventilation should be available. The HVAC system for the building should be operational and provide a consistent temperature of 65-85°F (air and sub-floor) and humidity levels should be between 40-65% for a minimum of 72 hours prior to the installation. These conditions must be maintained to ensure the long-term success and performance of the installation.

1. Flooring and adhesive should be acclimated to the job site conditions for a minimum of 24 hours prior to the installation.
2. Be familiar with the recommendations and any special instructions from the flooring manufacturer before beginning the installation. Follow the flooring manufacturer's specific recommendations regarding sub-floors and seam sealing.
3. Refer to the information above for specific information regarding sub-floor preparation and site conditions.
4. Spread the adhesive with the appropriate trowel as defined above. Allow the appropriate dwell or open time. Lay the carpet into the adhesive as to minimize bubbles and wrinkles.
5. Roll the flooring with a three-section roller [Carpet - 75lb. for direct glue and 35lb. double-glue; Sheet vinyl – 100lb.] to ensure adequate transfer. Wet adhesive transfer to the flooring must be 100%.
6. Roll the flooring "north to south" and "east to west" from center to edge forcing out air pockets and eliminating wrinkles.

Specific Technical Data:

- Base: SBR-resin emulsion
- Color: yellow-tan
- Flammability: Non-flammable

- Shelf Life: One year from date of manufacture in an unopened container
- Freeze-Thaw Stable: If frozen, allow the adhesive to thaw at room temperature. Do NOT stir or agitate while frozen. Stability and spread-ability can be reduced if frozen. For best results do not allow the adhesive to freeze.
- Clean-up: Remove wet adhesive with damp cloth (plain water). Use AAT-197 Adhesive Remover for dried adhesive.
- VOCs: 0 g/l (Calculated per Ca. Rule 1168); Solvent free
- Not recommended for exterior installations.

NOTE: We recommend installers follow the guidelines set forth in the latest version of the CRI's *Carpet Installation Standard - 104*. Before placing the carpet, the adhesive must be allowed an open or dwell time appropriate for the carpet backing, jobsite and sub-floor conditions. It is extremely important to maintain recommended notch depth, width and spacing. The proper notch depth is that which will produce adhesive ridges that affect a 100% transfer to both the substrate and the carpet backing to include the inner recesses of the texture of the back.

May 16, 2016



Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

1 Identification

- **Product identifier**
- **Trade name:** AAT-270
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Advanced Adhesive Technologies
424 South Spencer Street
Dalton, GA 30721
+1 (800) 228-4583
- **Emergency telephone number:**
CHEMTREC USA +1 (800) 424-9300 & INTERNATIONAL +1 (703) 527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning
- **Hazard-determining components of labeling:**
1,2-benzisothiazol-3(2H)-one
ethyl acrylate
- **Hazard statements**
May cause an allergic skin reaction.
Suspected of causing cancer.
- **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

Trade name: AAT-270

(Contd. of page 1)

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 1

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 0

Fire = 1

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1332-58-7	Kaolin	40.68%
471-34-1	calcium carbonate	5.3%
140-88-5	ethyl acrylate	0.7%
2634-33-5	1,2-benzisothiazol-3(2H)-one	0.06%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

Trade name: AAT-270

(Contd. of page 2)

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	140 mg/m ³
471-34-1	calcium carbonate	45 mg/m ³
140-88-5	ethyl acrylate	8.3 ppm
57-13-6	urea	30 mg/m ³
141-43-5	2-aminoethanol	6 ppm

- **PAC-2:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	1,500 mg/m ³
471-34-1	calcium carbonate	210 mg/m ³
140-88-5	ethyl acrylate	36 ppm
57-13-6	urea	280 mg/m ³
141-43-5	2-aminoethanol	170 ppm

- **PAC-3:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	8,900 mg/m ³
471-34-1	calcium carbonate	1,300 mg/m ³
140-88-5	ethyl acrylate	240 ppm
57-13-6	urea	1,700 mg/m ³
141-43-5	2-aminoethanol	1,000 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

Trade name: AAT-270

(Contd. of page 3)

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

1332-58-7 Kaolin

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 2* mg/m³
E; as respirable fraction

471-34-1 calcium carbonate

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV TLV withdrawn

140-88-5 ethyl acrylate

PEL Long-term value: 100 mg/m³, 25 ppm
Skin

REL See Pocket Guide App. A

TLV Short-term value: 61 mg/m³, 15 ppm
Long-term value: 20 mg/m³, 5 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.

- **Breathing equipment:** Not required.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

Trade name: AAT-270

(Contd. of page 4)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

- **Flash point:** >112 °C (>233.6 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

- **Vapor pressure:** Not determined.

Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

- **Solubility in / Miscibility with**

Water:	Fully miscible.
--------	-----------------

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

- **Solvent content:**

Organic solvents:	0.3 %
Water:	22.3 %
VOC content:	0.30 %
	3.0 g/l / 0.03 lb/gal

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

Trade name: AAT-270

(Contd. of page 5)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

471-34-1 calcium carbonate

Oral	LD50	6,450 mg/kg (rat)
------	------	-------------------

140-88-5 ethyl acrylate

Oral	LD50	800 mg/kg (rat)
Dermal	LD50	1,834 mg/kg (rabbit)
Inhalative	LC50/4 h	2,180 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

140-88-5	ethyl acrylate	2B
----------	----------------	----

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

Trade name: AAT-270

(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **TSCA (Toxic Substances Control Act):**
All ingredients are listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

Trade name: AAT-270

(Contd. of page 7)

- **Proposition 65**

- **Chemicals known to cause cancer:**

140-88-5	ethyl acrylate
----------	----------------

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

57-13-6	urea	II
---------	------	----

- **TLV (Threshold Limit Value established by ACGIH)**

1332-58-7	Kaolin	A4
-----------	--------	----

140-88-5	ethyl acrylate	A4
----------	----------------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

140-88-5	ethyl acrylate
----------	----------------

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

1,2-benzisothiazol-3(2H)-one
ethyl acrylate

- **Hazard statements**

May cause an allergic skin reaction.
Suspected of causing cancer.

- **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 03/01/2018

Trade name: AAT-270

(Contd. of page 8)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Technical Department

· **Contact:** Technical Director

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2