

## Sprayer Components Order List

PART #	PART NAME
US-1-10	Universal Adhesive Sprayer (Includes 10 gallon tank - 8 gal. capacity), cart, extension wand, compressor (1.5 hp), 24' hose (3/8" diameter), 2 o-rings, 2 spray tips (1 each #80-10 and #80-06) and cleaning kit
US-1-16	Universal Adhesive Sprayer (Includes 16 gallon tank - 14 gal. capacity) and same components
#0108	10 Gallon Canister (8-gal. capacity) Includes all valves, pressure gauge, relief valve and muffler. Canister does not include discharge hose or air line.
#0116	16 Gallon Canister (14-gal. capacity) Same features as above
#0114	Two-Wheel Cart
#0115	Air Compressor (1.5hp DeVilbiss and 5-gal. air tank)
#0119	Pistol Grip
#0127	Extension Wand (27")
#0136	Extension Wand (36")
#0138	Discharge Hose (3/8" diameter, inside)
#0150	Discharge Hose (1/2" diameter, inside)
#80-06	Brass Tip
#80-10	Brass Tip
#0159	Tip Valve Body
#0161	Tip Lock Nut Collar
#0165	Stainless Steel Ball Valves
#0166	Tank Air Pressure Gauge
#0170	Pop-off Safety Valve
#0172	Hose Support Springs (3/8" hose)
#0173	Hose Support Springs (1/2" hose)
#0181	High Pressure Air Hose
#0187	O-rings (neoprene for lid)

## Adhesive Usage Quick Reference

TYPE OF ADHESIVE	AAT-299	AAT-332	AAT-372	AAT-677
Vinyl-Backed Carpet		X		X
Urethane Foam-Backed Carpet	X			X
Unitary Backings	X			X
Needlepunched and Woven Backs	X			X
Jute Backings and ActionBac™	X			X
Rubber-Backed Carpets	X			X
VCT			X	X
Vinyl-Backed Sheet Goods				X
Carpet Tiles		X	X	X
Carpet Pad to Floor (double-glue)	X	X	X	X

## Universal US-1 Sprayer Adhesive Coverage Rates Quick Reference

AAT-299 AND AAT-677	COVERAGE PER GALLON
Woven polypropylenes, Enhancer backs®, foam backs, Life Spar® and Premier Plus®	10-12 yds./gallon
Latex unitary, hot melt, Double Lock ActionBac®	8-10 yds./gallon
Double glue-downs, carpet to pad	5-8 yds./gallon
Pad to floor	20-23 yds./gallon
AAT-332	
Carpet tiles	250-300 sq. ft./gallon
PVC or urethane-backed six-foot carpets	180-200 sq. ft./gallon
Pad to floor	180-200 sq. ft./gallon
AAT-372	
Vinyl composition tile (VCT)	400 sq. ft./gallon
Pad to floor	180-200 sq. ft./gallon